


# intimus 100 In the Office

**Professional Data Shredders – a Synthesis of Technology, Performance and Design. All intimus® shredders are built from durable, precision engineered, high-performance components, designed for a long life of high volume usage. The product range covers all requirements from day-to-day office use up to High Security Shredding machines in use for destruction of classified material in line with all current legal requirements such as DIN 66399 or NSA 02/01. intimus® shredders carry various features which make them unique in user-friendliness and operating efficiency.**

- Low noise level
- Automatic start/stop with light barrier
- Automatic stop in case of overload
- Illuminated indicators for basket full, door open and paper jam
- Sealed dust-free design with robust wooden cabinet
- Mounted on rollers for flexible use



W/D/H 49 x 44 x 90 cm



100 CP5 | 100CP6 | 100 CP7

\*CP6, CP7 / 2

EcoLogic

Model	Shred size		Security level DIN 66 399		Shredding capacity* sheets		Cutting speed m/s	Throughput** sheets/min		Also shreds:								
	mm	l	P	F	O	T		H	E	70 g/m <sup>2</sup>	80 g/m <sup>2</sup>							
100 SP2	3.8	100	5+	2	-	-	2*	-	-	30-32	26-28	0.14	905	792	✓	-	✓	-
100 CP4	3.8 x 36	100	5+	4	1	-	4*	-	-	23-25	20-22	0.14	707	622	✓	-	✓	-
100 CP5	1.9 x 15	100	5+	5	2	-	-	-	-	15-17	13-15	0.14	481	424	✓	-	✓	-
* only ID cards																		
<b>High Security Shredder</b>																		
100 CP6	0.8 x 12	100	5+	6	3	-	6	-	-	12-14	10-12	0.14	396	339	-	-	✓	-
100 CP7	0.8 x 4.5	100	5+	7*	3	-	-	-	-	7-9	6-8	0.14	254	226	-	-	-	-
* NSA approved (NSA / CSS EPL 02/01)																		

Optional Equipment	Packing unit	Art. No.	Shredder oil for CP-models	Packing unit	Art. No.
PE bags intimus 100 and 120	50 pieces	99977	Bottle at 110 ml	6 bottles	88035

\* based on 70 g/m<sup>2</sup> A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply. It may be lower if the voltage is below the rated/nominal value.  
\*\* theoretical average performance paper/min